



Faculty of Engineering
University of Kragujevac



Ministry of Science, Technological
Development and Innovation

**11th International Congress
Motor Vehicles & Motors 2026
ECOLOGY -
VEHICLE AND ROAD SAFETY
- EFFICIENCY
Proceedings**



University of Kragujevac



Department for Motor Vehicles
and Motors



International Journal for Vehicle
Mechanics, Engines and
Transportation Systems

October 8th - 9th, 2026
Kragujevac, Serbia

**11th International Congress
Motor Vehicles & Motors 2026**

**ECOLOGY -
VEHICLE AND ROAD SAFETY
- EFFICIENCY**

BOOK OF PROCEEDINGS

October 8th - 9th, 2026
Kragujevac, Serbia

Publisher: The Faculty of Engineering of the University of Kragujevac
Serbia, 34000 Kragujevac, Sestre Janjić 6

For Publisher: Prof. Slobodan Savić, Ph.D.
Dean of the Faculty of Engineering

Editors: Prof. Danijela Miloradović, Ph.D.
Assist. prof. Nadica Stojanović, Ph.D.
The Faculty of Engineering of the University of Kragujevac

Technical preparation: Asisst. Prof. Nadica Stojanović, Ph.D.

Cover: Nemanja Lazarević

USB edition: Faculty of Engineering, University of Kragujevac, Kragujevac

ISBN: 978-86-6335-132-5

Year of publication: 2026.

Published on USB by: InterPrint
Aleksinačka St. nn, 34000 Kragujevac, Serbia

Number of copies: 100

CIP - Каталогизacija y yбликацији Народна библиотека Србије, Београд

629.3(082)(0.034.2)
621.43(082)(0.034.2)

INTERNATIONAL Congress Motor Vehicles & Motors (11 ; 2026 ; Kragujevac)

Ecology - Vehicle and Road Safety - Efficiency [Elektronski izvor] : proceedings
/ 11th international congress Motor vehicles & motors 2026, October 8th - 9th,
2026 Kragujevac, Serbia ; [editors Danijela Miloradović, Nadica Stojanović]. -
Kragujevac : University, Faculty of Engineering, 2026 (Kragujevac : InterPrint). -
1 USB fleš memorija ; 1 x 2 x 6 cm

Sistemska zahtevi: Nisu navedeni. - Nasl. sa nasl. strane dokumenta. - Tiraž 100.
- Bibliografija uz svaki rad.

ISBN 978-86-6335-132-5

a) Моторна возила – Зборници b) Моторни са унутрашњим сагоревањем -
- Зборници

COBISS.SR-ID 201905929

*Publishing of this USB Book of proceedings was supported by
Ministry of Science, Technological Development and Innovation of the Republic of Serbia*

Copyright © 2026 Faculty of Engineering, University of Kragujevac



This book is published online with Open Access and distributed under the terms
of the Creative Commons Attribution License 4.0 (CC BY 4.0).

SCIENTIFIC BOARD

President

Prof. Danijela Miloradović, Ph.D., UniKg, FE, Serbia

Secretaries

Assist. Prof., Slavica Mačužić Saveljić, Ph.D., UniKg, FE, Serbia

Assist. Prof., Saša Milojević, Ph.D., UniKg, FE, Serbia

Members

Prof. Oday Ibraheem Abdulah, ANUni, CoE, Baghdad, Iraq

Assist. Prof. Ali Belhocine, UniMSM, FST, Mascara, Algeria

Emeritus Prof. Giovanni Belingardi, Ph.D., PoliTo, Turin, Italy

Prof. Murat Ciniviz, Ph.D., SelUni, FT, Konya, Turkey

Prof. Adrian Clenci Ph.D., UniPolBU, Bucharest, Romania

Prof. Bruno Dalla Chiara, Ph.D., PoliTo, Turin, Italy

Assoc. Prof. Aleksandar Davinić, Ph.D., UniKG, FE, Kragujevac, Serbia

Prof. Miroslav Demić, Ph.D., UniKG, FE, Kragujevac, Serbia

Prof. Jovan Dorić Ph.D., UniNS, FTS, Novi Sad, Serbia

Prof. Mohamed Ali Emam, Ph.D., HUni, FE, Cairo, Egypt

Prof. Jasna Glišović, Ph.D., UniKG, FE, Kragujevac, Serbia

Prof. Valentina Golubović Bugarski, Ph.D., UniBL, FME, Banja Luka, RS, Bosnia and Herzegovina

Assoc. Prof. Ivan Grujć, Ph.D., UniKG, FE, Kragujevac, Serbia

Prof. Rosen Hristov, Ph.D., TU Varna, Varna, Bulgaria

Prof. Aleksandra Janković, Ph.D., UniKG, FE, Kragujevac, Serbia

Assoc. Prof. Aleksandar Jovanović, Ph.D., UniKG, FE, Kragujevac, Serbia

Prof. Emrullah Hakan Kaleli, Ph.D., YTU, Istanbul, Turkey

Prof. Janez Kopač, Ph.D., UniLJ, FME, Ljubljana, Slovenia

Prof. Jovanka Lukić, Ph.D., UniKG, FE, Kragujevac, Serbia

Assist. Prof. Slavica Mačužić Saveljić, Ph.D., UniKG, FE, Kragujevac, Serbia

Assist. Prof. Saša Milojević, Ph.D., UniKG, FE, Kragujevac, Serbia

Assist. Prof. Slobodan Mišanović, Ph.D., CPTC Belgrade, Belgrade, Serbia

Prof. Alexander Novikov, Ph.D., OSUni, Orel, Russian Federation

Prof. Sreten Perić, Ph.D., UniD, MA, Belgrade, Serbia

Prof. Radivoje Pešić, Ph.D., UniKG, FE, Kragujevac Serbia

Prof. Snezana Petković, Ph.D., UniBL, FME, Banja Luka, RS, Bosnia and Herzegovina

Prof. Ralph Puetz, Ph.D., LUniAS, Landshut, Germany

Prof. Dragan Ružić, Ph.D., UniNS, FTS, Novi Sad, Serbia

Prof. Mikhail Shatrov, Ph.D., MADI, Moscow, Russian Federation

Assoc. Prof. Aleksandar Stevanović, Ph.D., UniPitt, Pittsburgh, USA

Assist. Prof. Nadica Stojanović, Ph.D., UniKG, FE, Kragujevac, Serbia

Assoc. Prof. Boris Stojić, Ph.D., UniNS, FTS, Novi Sad, Serbia

Prof. Radoje Vujadinović, Ph.D., UniMN, FME, Podgorica, Montenegro

Assoc. Prof. Predrag Živanović, Ph.D., UniBG, FTTE, Belgrade, Serbia

ORGANIZATIONAL BOARD

President

Asst. Prof., Nadica Stojanović, Ph.D., UniKg, FE, Serbia

Secretaries

Assist. Prof., Slavica Mačužić Saveljić, Ph.D., UniKg, FE, Serbia

Assist. Prof., Saša Milojević, Ph.D., UniKg, FE, Serbia

Members:

Prof. dr Jovanka Lukić, UniKg, FE, Kragujevac, Serbia

Prof. dr Jasna Glišović, UniKg, FE, Kragujevac, Serbia

Assoc. Prof. dr Aleksandar Davinić, UniKg, FE, Kragujevac, Serbia

Assoc. prof. dr Aleksandar Jovanović, UniKg, FE, Kragujevac, Serbia

Assoc. prof. dr Ivan Grujić, UniKg, FE, Kragujevac, Serbia

MVM2026 CONGRESS ORGANIZERS

Faculty of Engineering of the University of Kragujevac
Department for Motor Vehicles and Motors, FE Kragujevac
International Journal "Mobility & Vehicle Mechanics"

MVM2026 CONGRESS PATRONS

Ministry of Science, Technological Development and Innovation of the Republic of Serbia
Faculty of Engineering of the University of Kragujevac

MVM2026 CONGRESS REVIEWERS

Prof. dr Oday Ibraheem Abdulah, UniBAG, CoE, Baghdad, Iraq
Assist. Prof. dr Ali Belhocine, UniMSM, FST, Mascara, Algeria
Emeritus Prof. dr Giovanni Belingardi, PoliTo, Turin, Italy
Assoc. Prof. dr Aleksandar Davinić, UniKG, FE, Kragujevac, Serbia
Prof. dr Miroslav Demić, UniKG, FE, Kragujevac, Serbia
Prof. dr Jovan Dorić, UniNS, FTS, Novi Sad, Serbia
Prof. dr Jasna Glišović, UniKG, FE, Kragujevac, Serbia
Prof. dr Valentina Golubović Bugarski, UniBL, FME, Banja Luka, RS, Bosnia & Herzegovina
Assoc. Prof. dr Ivan Grujić, UniKG, FE, Kragujevac, Serbia
Prof. dr Rosen Hristov, TU Varna, Varna, Bulgaria
Assoc. Prof. dr Aleksandar Jovanović, UniKG, FE, Kragujevac, Serbia
Prof. dr Janez Kopač, UniLJ, FME, Ljubljana, Slovenia
Prof. dr Jovanka Lukić, UniKG, FE, Kragujevac, Serbia
Assist. Prof. dr Slavica Mačužić Saveljić, UniKG, FE, Kragujevac, Serbia
Assist. Prof. dr Saša Milojević, UniKG, FE, Kragujevac, Serbia
Prof. dr Danijela Miloradović, UniKG, FE, Kragujevac, Serbia
Assist. Prof. dr Slobodan Mišanović, CPTC Belgrade, Belgrade, Serbia
Prof. dr Radivoje Pešić, UniKG, FE, Kragujevac, Serbia
Prof. dr Snezana Petković, UniBL, FME, Banja Luka, RS, Bosnia & Herzegovina
Prof. dr Dragan Ružić, UniNS, FTS, Novi Sad, Serbia
Assoc. Prof. dr Aleksandar Stevanović, UniPitt, Pittsburgh, USA
Assist. Prof. dr Nadica Stojanović, UniKG, FE, Kragujevac, Serbia
Assoc. Prof. dr Boris Stojić, UniNS, FTS, Novi Sad, Serbia

FOREWORD

For 47 years, a traditional international gathering - originally known as a Symposium and, since 2006, as the "Motor Vehicles and Motors" Congress - has been held biennially at the Faculty of Engineering (formerly the Faculty of Mechanical Engineering) of the University of Kragujevac. This year, the 11th International Congress "Motor Vehicles and Motors" took place in Kragujevac on October 8th–9th, 2026, under the traditional motto: "Ecology – Vehicle and Road Safety – Efficiency".

A large number of authors from both the country and abroad responded to the organizers' invitation, resulting in numerous high-quality submissions across the event's core areas: "Power Train Technology," "Vehicle Design and Manufacturing," "Vehicle Dynamics and Intelligent Control Systems," "Driver/Vehicle Interface, Information Systems, and Assistance Systems," and "Transport Challenges in Emerging Economies." Additionally, two topics were officially introduced for the first time: "Artificial Intelligence in Automotive Technology" and "Autonomous Vehicles".

A total of 63 papers were accepted for presentation following a rigorous peer-review process. The presentations were organized into sessions, including a newly introduced poster session dedicated to students and young researchers.

The Congress organizers extend their special gratitude to the distinguished scientists in the fields of motor vehicles and transportation who agreed to deliver three inspiring introductory lectures addressing the heart of contemporary issues in the sector: prof. dr Ralph Putz (Landshut University of Applied Sciences, Germany), prof. dr Aleksandar Stevanović (University of Pittsburgh, USA), and prof. dr. Isak Karabegović (Academy of Sciences and Arts of Bosnia and Herzegovina, Bosnia and Herzegovina).

We extend our sincere gratitude to the esteemed members of the Congress Scientific Committee—who also served as reviewers for the papers submitted for presentation—for their significant contribution to the overall quality of the accepted papers.

The organization of the Congress was once again supported by the Ministry of Science, Technological Development and Innovation of the Republic of Serbia, the Faculty of Engineering of the University of Kragujevac, and the International journal "Mobility & Vehicle Mechanics" and we sincerely thank them for their support.

Scientific Board and Organizational Board of MVM2026 Congress

PREDGOVOR

Već 47 godina, svake druge godine, na Fakultetu inženjerskih nauka (nekada Mašinskom fakultetu) Univerziteta u Kragujevcu održava se tradicionalan međunarodni skup, nekada nazivan Simpozijum, a od 2006. godine - Kongres „Motorna vozila i motori“. Ovogodišnji, 11. Međunarodni kongres „Motorna vozila i motori“ održan je u Kragujevcu od 8. do 9. oktobra 2026. godine, uz tradicionalni moto „Ekologija – Vozilo i bezbednost na putu – Efikasnost“.

Na poziv organizatora odazvao se veliki broj autora iz zemlje i inostranstva, što je donelo veliki broj prijavljenih kvalitetnih radova iz glavnih oblasti skupa: „Tehnologija pogonskog sistema“, „Dizajn i proizvodnja vozila“, „Dinamika vozila i inteligentni upravljački sistemi“, „Interfejs vozač/vozilo, informacioni sistemi i sistemi za pomoć“, „Transportni izazovi ekonomija u usponu“, uz prvi put zvanično promovisane teme – „Veštačka inteligencija u automobilskoj tehnologiji“ i „Autonomna vozila“.

Ukupan broj od 63 radova je prihvaćen za prezentaciju posle rigoroznog procesa recenziranja. Rad je organizovan po sekcijama, uz prvi put promovisanu poster sekciju namenjenu za studente i mlade istraživače.

Organizatori Kongresa su posebno zahvalni istaknutim naučnicima iz oblasti motornih vozila i saobraćaja koji su pristali da održe tri inspirativna uvodna predavanja koja zadiru u srž savremenih pitanja vezana za vozila i saobraćaj, a to su: prof. dr Ralph Putz (Landshut University of Applied Sciences, Nemačka), prof. dr Aleksandar Stevanović (University of Pittsburgh, SAD) i prof. dr Isak Karabegović (Akademija nauka i umjetnosti Bosne i Hercegovine, Bosna i Hercegovina).

Veliku zahvalnost dugujemo našim dragim članovima Naučnog odbora Kongresa, ujedno i recenzentima radova prijavljenih za prezentaciju na Kongresu, koji su mnogo doprineli ukupnom kvalitetu konačno prihvaćenih radova.

Organizaciju Kongresa i ovog puta su podržali: Ministarstvo nauke, tehnološkog razvoja i inovacija Republike Srbije, Fakultet inženjerskih nauka Univeziteta u Kragujevcu i Međunarodni časopis „Mobility & Vehicle Mechanics“, na čemu im se iskreno zahvaljujemo.

Naučni odbor i Organizacioni odbor Kongresa MVM2026

CONTENT

INTRODUCTORY LECTURES

MVM2026-IL1	Ralph Pütz	OPERATING COSTS OF PUBLIC TRANSPORT BUSES WITH DIFFERENT PROPULSION SYSTEMS AND VARIOUS TYPES OF RENEWABLE ENERGY OVER TIME – WHERE IS THE JOURNEY HEADING?	3
MVM2026-IL3	Isak Karabegović	COLLABORATIVE ROBOTICS AND ARTIFICIAL INTELLIGENCE IN THE AUTOMOTIVE INDUSTRY: SMART ASSEMBLY AND AUTOMATED QUALITY CONTROL	13

SECTION A Power Train Technology

MVM2026-003	Ivan Grujic Aleksandar Davinic Zeljko Djuric Jovan Doric Milan Eremija Attila Kiss Sunny Narayan	THE INVESTIGATION OF THE COMBUSTION PROCESS OF THE BLEND OF THE CONVENTIONAL DIESEL FUEL AND BIODIESEL MADE FROM THE WASTE GRAPE SEEDS	35
MVM2026-008	Željko Đurić Ivan Grujić Nadica Stojanović Snežana Petković Jelena Adžić Milan Eremija	EXPERIMENTAL INVESTIGATION OF THE COMBUSTION PROCESS AND EFFICIENCY OF A DIESEL ENGINE IN THE CASE OF BIODIESEL FUEL APPLICATION	41
MVM2026-011	Milan Eremija Ivan Grujić Danijela Miloradović Željko Đurić Svetko Milutinović Nadica Stojanović	EXPERIMENTAL ANALYSIS OF EXHAUST GAS TEMPERATURE DURING THE USE OF BIODIESEL FUEL	53
MVM2026-013	Krasimir Markov Hristo Stanchev	INVESTIGATION OF THE FUEL CONSUMPTION AND EMISSIONS OF A DIESEL ENGINE RUNNING ON DIESEL WITH AN ADDITIVE	61
MVM2026-015	Milan Eremija Zoran Ristikić Svetko Milutinović Mesud Ajanović	EXPERIMENTAL INVESTIGATION OF THE INFLUENCE OF TIRE PRESSURE ON THE ROLLING RESISTANCE COEFFICIENT OF COMMERCIAL VEHICLES	67
MVM2026-025	Marko Lučić Mirjana Grdinić-Rakonjac Radoje Vujadinović Vladimir Pajković Ivan Grujić	ENERGY USE IN MONTENEGRO'S ROAD TRANSPORT SECTOR: TRENDS, FUEL STRUCTURE AND DEPENDENCE ON PETROLEUM-BASED FUELS	77

MVM2026-030	Vladimir Kočović Živana Jovanović Pešić Miloš Pešić Jelena Đusić Dragan Džunić	TRIBOLOGICAL PERFORMANCE OF BRASS SURFACES LUBRICATED WITH NEW AND USED ENGINE OILS	85
MVM2026-034	Mihailo Đuković Saša Milojević Slobodan Savić Blaža Stojanović Horia Abaitancei	APPLICATION OF A RADIAL HYDRAULIC MOTOR IN ALTERNATIVE VEHICLE DRIVE SYSTEMS	91
MVM2026-036	Marko Kitanović Slobodan Popović Nenad Miljić Predrag Mrđa	EFFECTIVE MIXTURE COMPOSITION IN THE ANGULAR DOMAIN IN SUPERCHARGED DISI ENGINE WITH MULTIPLE INJECTIONS	111
MVM2026-037	Petar Markov Radivoje Pušara Dragan Peruničić	A SINGLE-RANGE POLYNOMIAL MODEL FOR TEMPERATURE-DEPENDENT MIXTURE PROPERTIES IN COMBUSTION ENGINES WITH VARIABLE EGR RATES	125
MVM2026-038	Dragan Peruničić Petar Markov Radivoje Pušara	MODELING OF SPECIFIC HEAT RATIO FOR DISI ENGINES WITH COMPLEX MIXTURE FORMATION AND HIGH EGR RATES	139
MVM2026-041	Predrag Mrđa Slobodan Popović Nenad Miljić Marko Kitanović	EXPERIMENTAL AND CFD-BASED INVESTIGATION OF VAPOUR POCKET FORMATION IN AN INTERNAL COMBUSTION ENGINE COOLING SYSTEM	155
MVM2026-042	Nenad Miljić Predrag Mrđa Slobodan J. Popović	QUANTIFYING IMEP EVALUATION ERROR INDUCED BY PIEZOELECTRIC PRESSURE SENSOR AGEING IN INTERNAL COMBUSTION ENGINE INDICATION	165
MVM2026-051	Saša Milojević Marija Rafailović Michal Loman Branislav Šarkan Ján Vrábel Slobodan Savić	SAFETY AND OPERATIONAL CONSIDERATIONS FOR COMPOSITE HYDROGEN AND CNG STORAGE CYLINDERS IN VEHICLES	175
MVM2026-068	Mitar Mišić Stjepan Galamboš Boris Stojić Jovan Dorić Luka Sekicki	DEVELOPMENT OF AN ELECTRONIC MEASUREMENT SYSTEM FOR TURBOCHARGER WASTEGATE ACTUATOR RESPONSE-TIME TESTING	185
MVM2026-071	Mitar Mišić Stjepan Galamboš Jovan Dorić Boris Stojić Luka Sekicki	DESIGN AND IMPLEMENTATION OF A TEST BENCH FOR EVALUATING THE DYNAMICS OF PNEUMATIC WASTEGATE ACTUATORS	193

SECTION B

Vehicle Design and Manufacturing

MVM2026-006	Gordana Bogdanović Aleksandar Radaković Dragan Čukanović Petar Knežević Aleksandar Nešović	VARIATIONAL SHEAR CONTROL IN ESL–HSDT LAMINATES FOR AUTOMOTIVE STRUCTURES	203
-------------	--	---	-----

MVM2026-007	Gordana Bogdanović Aleksandar Radaković Petar Knežević Dragan Čukanović Marko Milošević	FATIGUE ANALYSIS OF MATERIALS AND METHODS FOR CYCLE COUNTING UNDER ARBITRARY LOAD HISTORIES	211
MVM2026-009	Julija Boskovic Ivan Grujic Stefan Djuric Nadica Stojanovic Bogdan Zivkovic Milan Ivkovic Suzana Petrovic Savic	DEVELOPMENT OF AN EXPERIMENTAL FIVE-AXIS CNC SYSTEM USING STEPPER MOTORS	219
MVM2026-012	Saša Vasiljević Jasna Glišović Slobodan Vasiljević	ANALYSIS OF EXPERIMENTAL METHODOLOGIES FOR TESTING INNOVATIVE BRAKE SOLUTIONS	235
MVM2026-016	Ljubica Spasojević Zorica Djordjević Sonja Kostić Saša Jovanović	MODAL ANALYSIS OF A COMPOSITE CRANKSHAFT FOR AN INTERNAL COMBUSTION ENGINE (ICE)	245
MVM2026-017	Zvonko Petrović Suzana Petrović Savić Milica Tufegdžić Nikola Kostić Milena Petrović	MATHEMATICAL MODELING OF HYDRAULIC DRIVE FOR THE MITSUBISHI RV-2FRL INDUSTRIAL ROBOT: INFLUENCE OF MOMENT OF INERTIA ON SERVO VALVE RESPONSE TIME	253
MVM2026-022	Marko Delić Vesna Mandić Nada Ratković Nikola Komatina Dušan Arsić Nikola Kastratović	ANALYSIS OF THE INFLUENCE OF IMPORTANT FORMING PARAMETERS IN SHEET METAL STAMPING IN AUTOMOTIVE INDUSTRY USING FEA	267
MVM2026-024	Milan Simonović Dragan Adamović Đorđe Ivković Marko Simonović	ANALYSIS OF THE POSSIBILITY OF PREDICTING THE TENSILE STRENGTH OF ADVANCED STRUCTURAL STEELS USED IN THE AUTOMOTIVE INDUSTRY USING ARTIFICIAL NEURAL NETWORKS WITH DIFFERENT NUMBERS OF NEURONS IN THE HIDDEN LAYER	275
MVM2026-026	Nenad Petrović Živana Jovanović Pešić Dragan Džunić Vladimir Kočović Strahinja Milenković	CREATING CURVED MESHES BY HEAT-FORMING 3D-PRINTED PARTS	287
MVM2026-050	Danijela Tadić Jasna Glišović Nikola Komatina	COMPARATIVE ANALYSIS OF OBJECTIVE CRITERIA WEIGHTING METHODS FOR ELECTRIC VEHICLE EVALUATION	293
MVM2026-052	Dragan Čukanović Gordana Bogdanović Aleksandar Radaković Petar Knežević	APPLICATION, MODELLING AND BENDING ANALYSIS OF COMPOSITE LAMINATES IN MODERN VEHICLES	303
MVM2026-053	Mihajlo Jevtić Aleksandra Obradović Bogdan Todorović Nebojša Hristov Damir Jerković	FINITE ELEMENT ANALYSIS OF STRUCTURAL SUPPORT REACTIONS IN WHEELED MOBILE PLATFORM UNDER HIGH-INTENSITY IMPULSIVE LOADING	311

MVM2026-059	Dušan Milojević Nikola Kotorčević Đorđe Damljanović Nikola Živčević Dušan Arsić Fatima Živić	EFFECTS OF UNIT CELL GEOMETRY AND STRUT THICKNESS ON THE COMPRESSIVE BEHAVIOR OF 3D-PRINTED MECHANICAL METAMATERIALS	321
MVM2026-060	Nebojša Arsić Nenad Kostić Nenad Petrović Nenad Marjanović	APPLICATION OF 3D SCANNING AND CAD DEVIATION ANALYSIS AS A BASIS FOR PRESS TOOL OPTIMISATION IN THE AUTOMOTIVE INDUSTRY	325
MVM2026-061	Sandra Gajević Slavica Miladinović Nikola Mitrović Zorica Djordjević Saša Milojević Blaža Stojanović	APPLICATION OF LAMINATED COMPOSITES IN THE AUTOMOTIVE, AVIATION AND MARINE INDUSTRY	333
MVM2026-067	Luka Milić Ilija Vidović Matija Simanić Momir Drakulić Aleksandar Đurić	ADDITIVE MANUFACTURING AS A FABRICATION METHOD FOR A LIGHTWEIGHT TRACKED ROBOT PLATFORM	345
MVM2026-070	Dobrovoje Čatić Vladimir Čatić	A COMBINED FTA-FMEA PROCEDURE FOR PRODUCT DEVELOPMENT	355
MVM2026-073	Milan Blagojević Milan Bojović Živče Šarkočević	REVERSE ENGINEERING OF A COMPLETE VEHICLE FOR THE DEVELOPMENT OF A MODULAR VEHICLE PLATFORM	363
MVM2026-076	Nenad Miloradović Rodoljub Vujanac Mirjana Piskulić	WAREHOUSE SYSTEMS IN THE AUTOMOTIVE INDUSTRY: A COMPARATIVE STUDY OF STORAGE SYSTEMS, HANDLING EQUIPMENT AND SAFETY CLEARANCE	369

SECTION C

Vehicle Dynamics and Intelligent Control Systems

MVM2026-001	Miroslav Demić Mikhail P. Malinovsky Andrija Vujičić	THEORETICAL-EXPERIMENTAL APPROACH TO THE DEVELOPMENT OF A METHOD FOR IDENTIFYING THE HEAT DISSIPATION RATE OF MOTOR VEHICLE SHOCK ABSORBERS	379
MVM2026-002	Aleksandar Jovanović Katarina Kukić Ana Uzelac Dušan Teodorović	DEEP Q-LEARNING ALGORITHM FOR TRAFFIC CONTROL AT A DISPLACED LEFT-TURN INTERSECTION	393
MVM2026-014	Boris Stojić Nebojša Nikolić Luka Sekicki	A FLEXIBLE COMPUTATIONAL MODEL FOR FUEL CONSUMPTION ESTIMATION IN ARBITRARY VEHICLE DRIVING CYCLES	403
MVM2026-018	Dušan Opsenica Ivan Blagojević Saša Mitić	THE INFLUENCE OF ELECTRIC VEHICLE CONFIGURATION ON VEHICLE DYNAMIC CHARACTERISTICS	413
MVM2026-023	Snežana Petković Valentina Golubović Bugarski Jelena Adžić Milan Eremija	ANALYSIS OF PARAMETERS INFLUENCING ROAD TANKER ROLLOVER	425

MVM2026-028	Momir Drakulić Aleksandar Đurić Sreten Perić	SENSITIVITY ANALYSIS OF A TERRAMECHANICS MODEL OF TRACK- TERRAIN INTERACTION WITH RESPECT TO VEHICLE DESIGN PARAMETERS	435
MVM2026-031	Marko Simonović Dragan Adamović Đorđe Ivković Milan Simonović	SELECTION OF MATERIALS FOR FRICTION COMPONENTS OF THE BRAKE MECHANISM	447
MVM2026-032	Zoran Papić Nenad Saulić Milja Simeunović	PREDICTION OF EES VALUES IN VEHICLE IMPACTS USING AI	461
MVM2026-035	Marijana Jeremić Lazar Krstić Miloš Ivanović Mihailo Lazarević Milan Matijević	DIGITAL TWIN DESIGN FOR TORSIONAL STIFFNESS ESTIMATION IN MOTOR-LOAD OSCILLATORY SYSTEMS USING PHYSICS- INFORMED NEURAL NETWORKS	471
MVM2026-040	Nebojša Jovičić Angelina Cvetanović Goran Bošković	EVALUATING THE EFFICIENCY OF OPTIMIZED WASTE COLLECTION ROUTES USING DATA ENVELOPMENT ANALYSIS	485
MVM2026-046	Aikaterini Zafeiri Clio Vossou Dimitrios Koulocheris	FLUID-STRUCTURE INTERACTION IN A TANK VEHICLE TRANSPORTING LIQUID FUEL	497
MVM2026-048	Ognjen Jovanović Milan Matijević	APPLICATION OF THE TIA PORTAL ENVIRONMENT FOR SOFTWARE-IN-THE-LOOP SIMULATION OF PLC CONTROL OF A FIRST- ORDER DYNAMIC SYSTEM	507
MVM2026-058	Nikola Gunić Hana Stefanović Milan Matijević	A NEW GENERATION OF WHEEL POSITION AND SPEED INTELLIGENT SENSORS FOR MOTOR VEHICLES	523
MVM2026-065	Danijela Miloradović Jasna Glišović Jovanka Lukić Nadica Stojanović	CONDITIONAL SPECTRAL ANALYSIS OF VEHICLE VIBRATION DATA	529
MVM2026-066	Matija Simanić Ilija Vidović Luka Milić Momir Drakulić Aleksandar Đurić	SIMULATION-BASED MOTION ANALYSIS OF A LIGHTWEIGHT TRACKED ROBOT USING WEBOTS	541
MVM2026-075	Branko Miličić Nikola Frlić Sekulić Miloš Mitrović Ivan Blagojević	IDENTIFICATION OF EFFECTIVE THERMO- PNEUMATIC TIRE PARAMETERS FROM REAL- WORLD ROAD TEST DATA	553

SECTION D

Driver/Vehicle Interface, Information and Assistance Systems


MVM2026-005	Slobodan Mišanović	THE INFLUENCE OF ENERGY DEMAND FOR PASSENGER COMPARTMENT CLIMATE CONTROL OF THE ENERGY EFFICIENCY OF ELECTRIC BUS	567
MVM2026-019	Dragan Ružić Miloš Vujković	DETERMINING THE FUEL CONSUMPTION REQUIRED FOR AIR-CONDITIONING OF A PASSENGER CAR UNDER REAL-WORLD CONDITIONS	579

MVM2026-020	Dragan Stojadinović Aleksandar Đurić Snežana Jovanović Miroslav Jovanović	THE INFLUENCE OF SEAT DESIGN AND SURFACE TYPE ON THE LEVEL OF VIBRATIONS EXPERIENCED BY A TRUCK DRIVER	589
MVM2026-063	Slavica Mačužić Saveljić Ognjen Matić Igor Saveljić	MACHINE LEARNING-BASED PREDICTION AND EXPLAINABILITY OF DRIVER DISCOMFORT AND FATIGUE: A DATA-DRIVEN EXTENSION OF A RAMSIS-BASED DIGITAL HUMAN MODEL STUDY	599
MVM2026-072	Jovanka Lukić Jasna Glišović Danijela Miloradović	COMPONENT COHERENCE-BASED ASSESSMENT OF MASKING EFFECTS IN TWO- DIRECTIONAL WHOLE-BODY VIBRATION	609
MVM2026-074	Milan Blagojević Saša Milojević Živče Šarkočević Ivica Čamagić Dragan Lazarević	FIAT 500L REAR IMPACT PERFORMANCE IN EURO NCAP AND IIHS ASSESSMENTS	623

SECTION E

Transport Challenges in Emerging Economies

MVM2026-033	Janez Kopač Franci Pušavec	HIGHWAY ROAD TRAPS AS HIDDEN SOURCES OF CRASH RISK	633
MVM2026-044	Nadica Stojanović Ali Belhocine Ivan Grujić Željko Đurić Suzana Petrović Savić Oday I. Abdullah	THE IMPACT OF “DRUNK BUSTERS” ON THE ADEQUATE PERFORMANCE OF TASKS	645
MVM2026-055	Vladimir Vukašinović Dušan Gordić Vanja Šuštersiћ Mladen Josijević	SUSTAINABLE BIOFUELS FOR THE DECARBONISATION OF THE TRANSPORT SECTOR IN CITIES	659
MVM2026-062	Goran Bošković Nebojša Jovičić Angelina Cvetanović Saša Milojević	ASSESSMENT OF THE NUMBER OF END-OF- LIFE VEHICLES IN THE REPUBLIC OF SERBIA	669
MVM2026-064	Bojana Bošković Nadica Stojanović Saša Babić Milena Petrović Anđela Egerić	PREDICTION AND TIME-SERIES ANALYSIS OF ROAD DEATHS PER MILLION INHABITANTS IN THE REPUBLIC OF SERBIA AND THE EUROPEAN UNION FOR THE PERIOD 2012 TO 2030	677
MVM2026-069	Saša Jovanović Zorica Đorđević Danijela Nikolić Lozica Ivanović Saša Milojević	A SAW-BASED DECISION SUPPORT MODEL FOR THE SELECTION OF NEW AND USED PASSENGER CARS	691



The 11th International Congress
Motor Vehicles & Motors 2026
Kragujevac, Serbia
October 8th - 9th, 2026



MVM2026-051

<https://doi.org/10.24874/CMVM2026.051>
Technical paper

Saša Milojević¹

Marija Rafailović²

Michal Loman³

Branislav Šarkan⁴

Ján Vrábek⁵

Slobodan Savić⁶

SAFETY AND OPERATIONAL CONSIDERATIONS FOR COMPOSITE HYDROGEN AND CNG STORAGE CYLINDERS IN VEHICLES

ABSTRACT: The increasing adoption of compressed natural gas (CNG) and hydrogen as alternative automotive fuels has intensified the demand for reliable and safe high-pressure storage technologies. Composite pressure cylinders offer an efficient solution for onboard gaseous fuel storage owing to their high strength-to-weight ratio, corrosion resistance, and favorable fatigue performance. This paper presents a comprehensive analysis of operational conditions, installation requirements, inspection procedures, maintenance practices, and safety considerations associated with Type-3 composite cylinders used for onboard storage of CNG and hydrogen in road vehicles. The study examines the effects of pressure cycling, temperature variations, environmental exposure, mechanical damage, and operational handling on cylinder integrity and service life. Particular attention is given to mounting systems, thermal pressure relief devices, inspection methodologies, and damage assessment criteria. Additionally, the paper examines fueling and defueling procedures, risk mitigation measures, and end-of-life management practices. The analysis highlights the critical factors affecting cylinder reliability and identifies key safety measures necessary for safe long-term operation. The findings contribute to improved operational reliability, risk management, and safety performance of modern alternative-fuel vehicle systems.

¹ Dr Saša Milojević, prof. assist. Faculty of Engineering University of Kragujevac, Kragujevac 34000, Sestre Janjić 6, Serbia, sasa.milojevic@kg.ac.rs,  <https://orcid.org/0000-0003-0569-047X>

² Ms. Marija Rafailović, PhD student. Faculty of Engineering University of Kragujevac, Kragujevac 34000, Sestre Janjić 6, Serbia, marija.rafailovic@kg.ac.rs,  <https://orcid.org/0009-0001-2132-9249>

³ Dr Michal Loman, prof. assist. University of Žilina, Faculty of Operation and Economics of Transport and Communications, 010 26 Žilina, Univerzitná 8215/1, Slovakia, michal.loman@uniza.sk,  <https://orcid.org/0000-0003-4300-3802>

⁴ Dr Branislav Šarkan, prof. assist. University of Žilina, Faculty of Operation and Economics of Transport and Communications, 010 26 Žilina, Univerzitná 8215/1, Slovakia, branislav.sarkan@uniza.sk,  <https://orcid.org/0000-0002-5036-9223>

⁵ Dr Ján Vrábek, prof. assist. University of Žilina, Faculty of Operation and Economics of Transport and Communications, 010 26 Žilina, Univerzitná 8215/1, Slovakia, jan.vrabel@uniza.sk,  <https://orcid.org/0000-0002-1407-2924>

⁶ Dr Slobodan Savić, full prof. Faculty of Engineering University of Kragujevac, Kragujevac 34000, Sestre Janjić 6, Serbia, ssavic@kg.ac.rs,  <https://orcid.org/0000-0001-6609-4845>

KEYWORDS: Composite pressure cylinders; Hydrogen storage; compressed natural gas (CNG); vehicle safety; inspection and maintenance

BEZBEDNOSNI I EKSPLOATACIONI ASPEKTI PRIMENE KOMPOZITNIH REZERVOARA ZA SKLADIŠTENJE VODONIKA I KPG U VOZILIMA

REZIME: Sve veću primenu komprimovanog prirodnog gasa (KPG) i vodonika kao alternativnih goriva za vozila prati i potreba za pouzdanim i bezbednim tehnologijama za skladištenje ovih gasova pod visokim pritiskom. Kompozitni rezervoari predstavljaju efikasno rešenje za skladištenje gasovitih goriva u vozilima zbog povoljnog odnosa mase i zapremine, adekvatne čvrstoće, otpornosti na koroziju, kao i dobre otpornosti na zamor materijala. U radu je data analiza uslova eksploatacije, zahteva za ugradnju, postupaka kontrole, održavanja i sistematizovani su osnovni uslovi sa aspekata bezbedne primene kompozitnih rezervoara tipa 3 za skladištenje KPG-a i vodonika u motornim vozilima. Razmatrani su uticaji cikličnih promena pritiska, temperaturnih promena i drugih uslova okoline, kao i mehaničkih oštećenja i načina rukovanja na konstrukciju i radni vek rezervoara. Posebna analiza je izvršena u delu uslova za pričvršćenje rezervoara, ugradnje uređaja i opreme za rasterećenje pritiska, metoda kontrole i kriterijuma za eventualnu procenu oštećenja rezervoara. Takođe su analizirani uslovi za bezbedno punjenje i pražnjenje rezervoara za potrebe servisiranja i održavanja, u cilju smanjenja rizika, i istraživano je postupanje sa rezervoarima na kraju radnog veka. Analizom su identifikovani ključni faktori koji utiču na pouzdanost rezervoara i definisane su osnovne mere i uslovi u cilju njihove bezbedne i dugoročne eksploatacije.

KLJUČNE REČI: Kompozitni rezervoari pod pritiskom, skladištenje vodonika, komprimovani prirodni gas (KPG), bezbednost vozila, kontrola i održavanje

INTRODUCTION

Composite high-pressure cylinders are increasingly used in automotive applications for the storage of compressed natural gas (CNG) and hydrogen. The safe operation of these systems is governed by defined pressure, temperature, and service conditions established by the applicable standards and certification requirements. Accordingly, the cylinders must be operated within their specified design and permissible operating limits throughout their service life. The Type-3 cylinders considered in this research feature a seamless 6061 aluminium alloy liner that is completely enclosed by a carbon-fiber/epoxy composite overwrap, providing the required structural reinforcement and pressure resistance, Figure 1 (Milojević, 2017; Luxfer Gas Cylinders, 2018).



Figure 1 Design of a Type 3 Composite Cylinder (AA6061 aluminium liner with carbon fibre/epoxy overwrap)

In general, the applicable design and safety requirements are specified by the relevant standards and regulations, including ISO 11439 and UN ECE 110R for natural gas applications, as well as Regulation (EU) 2019/2144 and UN Regulation No. 134 for hydrogen-fueled systems (UNECE, 2018; ISO, 2013; European Parliament & Council of the European Union, 2019; UNECE, 2019).

The cylinders are designed for a nominal service pressure of 20 MPa, referenced to an ambient temperature of 15 °C. During refueling, the filling pressure must be controlled so that, after thermal stabilization, the cylinder pressure does not exceed the specified service pressure under the reference temperature conditions. Therefore, the pressure applied during filling should be adjusted according to the actual gas temperature to ensure compliance with the maximum permissible filling pressure. The following approximate relationships can be used for estimating the corresponding pressure conditions (Luxfer Gas Cylinders, 2018):

$$P_{\text{CNG}} = 176 + 1.6 \cdot T_{\text{CNG}} \quad (1)$$

$$P_{H_2} = 189 + 0.73 \cdot T_{H_2} \quad (2)$$

Where are:

P [bar] – the corresponding pressures; and T [°C] – the temperatures of CNG and hydrogen, respectively.

For natural gas applications, the actual cylinder pressure is additionally influenced by the composition of the gas. Regardless of the operating temperature, the filling pressure must remain below the absolute maximum limit of 26 MPa. Furthermore, the cylinders should only be filled using compressors whose maximum discharge pressure does not exceed 1.5 times the specified nominal service pressure.

Hydrogen can also be stored in gaseous form within pressure vessels at substantially higher pressures than those typically used for natural gas. For example, a nominal service pressure of 35 MPa is specified at an ambient temperature of 15 °C. During filling, the pressure should be controlled so that, following thermal stabilization, the cylinder pressure does not exceed the specified service pressure of 35 MPa under the reference temperature conditions (Luxfer Gas Cylinders, 2018).

For hydrogen storage systems, the filling pressure is subject to an absolute upper limit of 43.75 MPa, which must not be exceeded irrespective of the gas temperature. Accordingly, the pressure applied during the refueling process should be determined by taking into account the actual hydrogen temperature, thereby ensuring that the pressure remains within the permissible filling limit. The following approximate calculations can be employed to estimate the appropriate filling pressure under different temperature conditions (Luxfer Gas Cylinders, 2018):

$$P_{H_2} = 331 + 1.26 \cdot T_{H_2} \quad (3)$$

During handling, transportation, and storage, Type–3 cylinders should be depressurized and carefully protected against mechanical damage, particularly to the carbon–fiber overwrap and aluminum liner. Appropriate personal protective equipment should be used, while contact with valves, fittings, and pressure–relief devices should be avoided. Cylinders must be secured against rolling, impacts, and accidental dropping. During storage, they should be protected from excessive heat, moisture, corrosive environments, UV radiation, and surface abrasion, with suitable protective plugs used to prevent contamination of open ports. Appropriate lifting equipment should be employed when necessary.

Type–3 cylinders can withstand normal contaminants encountered in automotive environments; however, exposure to highly corrosive acids, alkalis, or abrasive materials should be avoided. No additional protective coating is recommended, as it could hinder the visual detection of damage to the reinforcing fibers. The existing epoxy surface layer provides adequate protection of the composite overwrap. Particular care should also be taken to prevent the ingress of water into the cylinder, since moisture contamination may adversely affect its service life.

The operating temperature limits for CNG and hydrogen cylinders are defined by the applicable standards and regulations, including ISO 11439, UN ECE 110R, and Regulation (EU) 2019/2144 and UN Regulation No. 134. Under these conditions, the settled gas temperature may range from (–40) – 65 °C for CNG and up to 85 °C for hydrogen. The corresponding allowable temperature range for the cylinder materials extends from (–40) – 82 °C for CNG and up to 85 °C for hydrogen. For CNG cylinders, any local or transient temperature increase above 65 °C must be limited in duration and extent so that the gas temperature inside the cylinder remains below the specified maximum (UNECE, 2018; ISO, 2013; European Parliament & Council of the European Union, 2019; UNECE, 2019).

The cylinders are suitable for CNG, compressed hydrogen, and hydrogen–gas mixtures. The composition of CNG shall meet the requirements specified in ISO 11439 and UN ECE 110R, while Compressed hydrogen shall comply with the fuel quality requirements specified in ISO 14687:2025 (UNECE, 2018; ISO, 2013, 2025).

The service life of the cylinders is limited to approximately 15–20 years from the date of final inspection, depending on the applicable national requirements and specified annual filling cycles. The expiration date is indicated on the cylinder label. Once the specified service life or maximum number of filling cycles is reached, the cylinder must be permanently withdrawn from service. For CNG cylinders, the allowable number of fillings is limited to 1000 cycles per year of service life, while hydrogen cylinders are limited to 5000 filling cycles (Luxfer Gas Cylinders, 2018).

For hydrogen cylinders, the applicable regulations may permit a lower maximum number of filling cycles when an appropriate monitoring and control system is implemented. In such cases, the specified cycle limit is marked on the cylinder label, Figure 2, and the cylinder must be withdrawn from service once this limit has been reached.

Periodic external visual inspections of the composite overwrap are required after installation or reinstallation to identify possible defects. The inspection frequency and procedures shall comply with the applicable national standards and regulations; for CNG cylinders, UN ECE 110R specifies an interval of at least 48 months after the vehicle is placed into service. Shorter intervals may apply depending on the cylinder type and applicable type–

approval requirements. Inspections should be performed according to ISO 19078:2013 or national standards (UNECE, 2018; ISO, 2013).



Figure 2 Examples of CNG and Hydrogen Cylinder Labels

Routine hydraulic pressure testing is generally not required. Where such testing is mandated by national regulations, only appropriately treated water should be used, with chloride removal and suitable corrosion inhibitors, while exposure time should be minimized to protect the AA6061 aluminum liner from corrosion.

Cylinders that have been subjected to a vehicle collision shall undergo a re-inspection conducted by an agency authorized by the manufacturer and, where applicable, by the relevant regulatory authority. If the inspection confirms that the cylinder has not sustained any impact-related damage, it may be returned to service. However, if any damage resulting from the collision is identified, the cylinder shall be returned to the manufacturer for further assessment and evaluation.

Cylinders exposed to fire shall be immediately removed from service and shall not be returned to service unless their safety and structural integrity have been verified through an appropriate inspection and assessment. A cylinder may have been adversely affected by fire or excessive heat without exhibiting any visible signs of damage. Therefore, the prescribed inspection and assessment procedures shall be followed to ensure that the cylinder remains safe for further service.

CYLINDER AND EQUIPMENT INSTALLATION REQUIREMENTS

The cylinders shall be installed in accordance with the applicable installation requirements for the specific model. The installer is responsible for ensuring adequate protection of cylinder valves, pressure relief devices (PRD), and connections, in compliance with the applicable national standards and regulations.

All components must be suitable for a working pressure of at least the nominal service pressure of the cylinder, i.e., 20 or 35 MPa, depending on the cylinder type. Components used in accordance with UN ECE 110R and the relevant requirements for hydrogen vehicles must be approved for a working pressure corresponding to at least the maximum filling pressure of 26 or 43.75 MPa, respectively (Luxfer Gas Cylinders, 2018).

For fire safety, each cylinder must be equipped with an appropriate PRD compatible with the cylinder type and approved in accordance with the relevant standards.

Valves and End Plugs with O-Ring Seals

All valves and end plugs shall be provided with an O-ring sealing seat and shall have at least 7 engaged threads for 20 MPa cylinders and 11 engaged threads for 35 MPa cylinders. The components shall be tightened to the specified torque. Tapered threads shall not be used (Luxfer Gas Cylinders, 2018).

Before installation, the valve or end plug, mating threads, and sealing surfaces shall be inspected for damage and cleaned with a suitable detergent or solvent using a nylon brush. The surfaces shall then be dried with a clean cloth and kept free of dirt and debris. The specified O-ring shall be selected according to Table 1 and installed carefully without damage. Other O-rings shall not be used without prior qualification.

Table 1 Example: O-Ring Specifications and Tightening Torques for 1.125" and 2.0" Threads

Thread designation	O-ring dimensions [mm] (inside diameter x cross-section diameter)	Torque [Nm] 20 / 35 MPa cylinder series
1.125 – 12 UNF	28.17 x 3.53	217 (± 14) / 240 (± 10)
2.0 – 12 UN	50.39 x 3.53	305 (± 15) / 320 (± 10)

The valve or end plug shall be manually screwed into the cylinder port and tightened to the specified torque using appropriate tools. The required tightening torques shall comply with the values given in Table 1. After tightening, a

suitable torque-indicating compound shall be applied to the external joint between the end plug and cylinder neck to confirm completion of the installation (Luxfer Gas Cylinders, 2018).

For hydrogen service, the use of O-ring lubricant or anti-seize compound should be minimized to avoid potential gas contamination. If required, a thin film of suitable O-ring lubricant may be applied to the O-ring. A small amount of copper-free anti-seize compound may be applied to the first threads, as shown in Figure 3.a, while avoiding contact with the O-ring.




Figure 3 (a) Application of Anti-Seize Compound to the Valve Thread; (b) Typical Valve and TPRD Assembly

Pressure Relief Devices

Thermally activated pressure relief devices (TPRDs) shall be incorporated into the cylinder piping system to provide controlled pressure relief in the event that the cylinder is subjected to fire or excessive heat, Fig.3.b. The required number and configuration of TPRDs shall be specified in the applicable installation drawing. The TPRD discharge outlets shall remain unobstructed and shall not be blocked, sealed, or covered by adjacent components or attachments.

For longer cylinders, a middle-plug TPRD may be installed at the center of the cylinder and connected to the valve or end plug by a dedicated TPRD pipe, Figure 4.

The TPRD pipe remains under cylinder pressure even when the valve is manually and/or electrically closed. Installation and servicing shall therefore be performed only by personnel trained in compression fitting installation.

The TPRD and pipe shall be positioned and installed in accordance with the applicable installation drawing and the manufacturer's instructions. The pipe shall be cleaned immediately before installation. The TPRD shall be secured using a saddle clamp with a rubber strip between the clamp and cylinder surface. The clamp shall be correctly positioned, tensioned, and locked in accordance with the manufacturer's instructions, Figure 4.



Figure 4 TPRD Pipe, Middle Plug and Saddle Bracket on Bus-Mounted Cylinders

A minimum clearance of 5 mm shall be maintained between the TPRD pipe and the cylinder surface. Where necessary, a soft elastomeric support may be installed between the pipe and cylinder, Figure 4 (Luxfer Gas Cylinders, 2018).

Cylinder Installation and Mounting

The cylinder, cylinder assembly, or cylinder rack, including the associated safety devices and complying with UN ECE 110R or Regulation (EU) 2019/2144 and UN Regulation No. 134, shall be securely installed and restrained to withstand the specified accelerations and decelerations given in Table 2, without failure or loosening of the mounting system. Compliance shall be demonstrated by appropriate testing or calculation, using a mass representative of the fully equipped and filled cylinder, cylinder assembly, or cylinder rack (UNECE, n.d.; UNECE, 2019; ISO, 2025).


As example, neck mount brackets are designed to securely fasten CNG or hydrogen storage cylinders to automotive vehicles in a horizontal position, Figure 5. Where neck mounting is specified, the cylinder model number includes the designation "N" at the end. The Figure 5 also shows the installation position of the cylinder on the factory-mounted roof rack of the bus (Milojević, 2017; Milojević et al., 2025).

Table 2 Required Accelerations and Decelerations for Gas Cylinders

Motor Vehicle Categories	M1 and N1	M2 and N2	M3 and N3
Vehicle Acceleration:			
– In the Direction of Travel	20·g	10·g	6.6·g
– Perpendicular to the Direction of Travel	8·g	5·g	5·g

Motor Vehicle Categories: M1 with ≤ 9 passengers or N1 (for goods) ≤ 3.5 t;
M2 with > 9 passengers and ≤ 5 t or N2 (for goods) > 3.5 t and ≤ 12 t;
M3 with > 9 passengers and > 5 t or N3 (for goods) > 12 t

The brackets shall only be used within the conditions specified in this Statement of Service. Installation shall comply with the applicable requirements of ISO 11439 and UN ECE 110R for CNG cylinders, or Regulation (EU) 2019/2144 and UN Regulation No. 134 for hydrogen cylinders (UNECE, n.d.; ISO, 2013; UNECE, 2019; ISO, 2025).

**Figure 5** Cylinder Neck Mount Assembly and Installation of the Cylinder Rack on the Roof of a City Bus

Cylinders are installed using two neck–mounting brackets that secure the extended cylinder necks. One end of the cylinder is rigidly restrained, while the opposite end is allowed to slide within the bracket to accommodate dimensional changes caused by variations in temperature and internal pressure, Figure 5. When properly installed, the fixed neck–mounting bracket prevents longitudinal movement of the cylinder neck within the bracket up to a maximum longitudinal load of 17 kN. This load corresponds to the following weights for a fully filled cylinder, Table 3 (Luxfer Gas Cylinders, 2018):

Table 3 Permissible Total Cylinder Weight According to ECE R110, (EC) No. 79/2009, and (EC) No. 406/2010

Acceleration	20·g	10·g	6.6·g
Maximum Permissible Weight of a Filled Cylinder [kg]	86	173	262

Max. Permissible Weight of a Filled Cylinder = 17 kN / (9.81 m/s² x acceleration)

A neck mount bracket set consists of a fixed bracket, a sliding bracket, and a pre–installed high–molecular–weight polyethylene bushing. The fixed bracket is installed on the cylinder neck with the cylinder serial number and bracket marking facing outward and upward, while the sliding bracket is installed on the opposite neck in the same orientation. The cylinder is then placed on the vehicle rack and rotated to position the fixed (valve) end as required. The neck position in the sliding bracket shall be adjusted to provide sufficient clearance for cylinder expansion caused by pressure and temperature variations Figure 5.

The M12 sliding and fixed bracket bolts shall be selected according to the working loads, with minimum property classes of 70 for stainless steel and 8.8 for steel bolts. The bolts shall be tightened to the specified torque, but not less than 70 Nm, and secured against loosening using an appropriate locking method. After tightening the fixed bracket, the cylinder position shall be checked and readjusted if necessary (Luxfer Gas Cylinders, 2018).

Cylinder Protection and Shielding Requirements

The cylinder shall be installed with suitable protection and shielding to prevent damage under vehicle operating conditions. The shielding shall protect the cylinder from road debris, contact with cargo, excessive heat, harmful vehicle fluids, and prolonged UV exposure.

The shielding shall be installed without direct contact with the cylinder and without creating areas where debris or liquids can accumulate. It shall also prevent contact between the cylinder and vehicle components such as the frame, body panels, brake lines, and exhaust system, thereby reducing the risk of abrasion and surface damage. Open–mesh shielding is generally preferred because it minimizes the accumulation of water and other liquids while allowing visual inspection of the cylinder.

No additional coating shall be applied to the composite cylinder if it could adversely affect the composite material or interfere with visual inspection. The shielding and mounting arrangement shall also ensure that the cylinder identification markings remain clearly visible, including the cylinder label and barcode, the dome sticker and barcode, and the serial–number marking on the cylinder neck, Figure 6.



Figure 6 Cylinder Serial Number Locations

A permanent electrical connection between the cylinder, including its attached components, and the vehicle shall be provided to prevent the accumulation of static electrical charge and minimise the risk of sparking that could ignite escaping gas.

CYLINDER AND MOUNTING SYSTEM INSPECTION AND MAINTENANCE

When filling, defueling, inspecting, or servicing cylinders and associated components containing pressurized hydrogen or natural gas, appropriate safety precautions shall be followed. Only trained and authorised personnel shall fill, defuel, inspect, or service cylinders and components containing pressurized hydrogen or natural gas, following the manufacturer's procedures and using appropriate protective equipment.

All potential ignition sources, including open flames and heat sources, shall be eliminated. Electrical connections shall be disconnected where necessary, and the system shall be properly grounded to prevent sparking. The system and its components shall always be assumed to be pressurized. Fittings and ports shall therefore be opened slowly, and work shall be stopped immediately if gas leakage occurs or excessive torque is required.

Particular care shall be taken when a potentially flammable gas mixture may be present. Hydrogen is flammable in air at concentrations of approx. 4–74%, while natural gas is flammable at approx. 5–15%. Systems containing potentially flammable mixtures shall not be operated, stored, or transported and shall be properly purged before further work. Electrical connections shall not be made to systems containing a potentially flammable mixture (Luxfer Gas Cylinders, 2018; Loman et al. 2026).

Preparation of Cylinders and Components for Inspection and Maintenance

Depending on the maintenance activity, the cylinder and associated components may require defueling and/or purging before work begins. For visual inspection and leak testing, where no mechanical work is performed, the cylinder assembly shall be properly grounded. If maintenance is performed without breaking connection seals, such as re-torquing fittings or end plugs, the assembly shall be grounded and defueled to prevent the ingress of air or debris. If connection seals must be broken, such as when replacing a valve or fitting, the cylinder or component shall be grounded, defueled, and purged before work begins.

The cylinder and associated components should be cleaned before visual inspection using clear or soapy water. Abrasive detergents and aggressive cleaning agents, such as acetone, solvents, or gasoline, shall not be used because they may damage the cylinder surface. A pressure washer may be used with a maximum spray pressure of 10 MPa and a minimum distance of 50 cm. The water jet shall not be directed at cylinder labels, solenoid valves, electrical connectors, or safety devices such as TPRDs (Luxfer Gas Cylinders, 2018).

Inspection of Cylinders and Components

Inspection is an essential safety measure for detecting damage to the cylinder or mounting system and identifying any adverse environmental effects during operation. Inspections shall be performed using appropriate tools, such as measuring instruments for determining defect dimensions, a flashlight, an adjustable mirror, and a cleaning cloth. Two types of inspections are specified: General Inspection and Certification Inspection, as summarized in Table 4.

The General Inspection is not mandatory but is recommended every 3 months to verify that the fuel storage system remains in good condition. It covers the mounting system and cylinder(s).

The mounting inspection shall verify that all brackets are undamaged and securely attached to the vehicle, with all bolts present and properly tightened. For belly-mounted systems, protection pads shall be present, in good condition, and each cylinder shall be securely restrained. Loose mounting components shall be re-secured in accordance with the applicable installation procedure. Damage to the mounting system may indicate vehicle accident involvement and requires a Certification Inspection. Missing or damaged components shall be replaced with approved parts.

Table 4 Inspection Categories Summary

Inspection Type	Description	Inspection Frequency
General Inspection	Performed by the driver, maintenance personnel, or other qualified service technician, this inspection is primarily visual and is intended to verify that the cylinder, mounting system, and piping are in good condition, properly secured, and free from visible damage.	Recommended every 3 months
Certification Inspection	Performed by trained personnel certified in accordance with applicable local regulations and requirements. This inspection provides a more detailed examination of the cylinder, mounting system, and piping.	Typically performed at commissioning and every 3–4 years, subject to local authority requirements.

The cylinders shall be inspected for signs of damage in accordance with the applicable inspection criteria, Table 5. Any indication of damage shall be assessed and appropriate corrective action determined. Minor cutting or abrasion limited to the outer pure epoxy resin layer is not considered critical and does not require further damage assessment.

Table 5 Cylinder Damage Types, Signs, and Potential Causes

Cylinder Damage Type	Signs of Damage	Potential Causes
Impact Damage	Dents, scratches, cracked or peeling laminate, or crazing (hairline cracks in the laminate)	Impact from a blunt object or dropping the cylinder
Cutting Damage	Cuts, scratches, gouges, or peeling laminate	Contact with a sharp or pointed object
Abrasion Damage	Scuffs, dull or whitish areas, or flat spots	Friction between the laminate and an object in contact with the cylinder
Fire or Excessive Heat Damage	Charred or discolored laminate, soft spots, blistering, or swelling	Exposure to direct flame, contact with an excessive heat source, or proximity to a high-temperature source
Weathering Damage	Cloudy appearance, discoloration, or soft spots	Exposure to UV radiation or water ingress through cracks in the laminate
Chemical Damage	Discoloration, soft spots, blistering, or swelling	Exposure to brake fluid or other corrosive fluids

The Certification Inspection is a detailed examination of the cylinder and mounting system performed by personnel certified in accordance with local regulations. The inspection frequency is determined by the relevant authorities and is typically every 4 years for CNG cylinders under UN ECE 110R and every 3 years for other cylinders. Following a vehicle accident, a Certification Inspection should be considered even if no visible damage is apparent (UNECE, n.d.; Milojević et al. 2025).

Before filling, the hazards associated with hydrogen and natural gas, including fire, explosion, and asphyxiation, shall be considered. Filling shall be performed in a well-ventilated area free of ignition sources, with appropriate leak testing, evacuation, and purging procedures to prevent the formation of flammable gas mixtures. Proper system design and operating procedures are essential for safe handling (Turek et al. 2024; Aldhafeeri et al. 2020).

Defueling shall be performed by controlled venting to approx. 0.2 MPa, preventing air ingress and safely discharging the gas through an appropriate venting or flare system. The procedure shall be performed outdoors in a controlled safety zone, with the system grounded, ignition sources eliminated, and appropriate protective equipment used (Luxfer Gas Cylinders, 2018).

CONCLUSIONS

The analysis confirms that the safe and reliable operation of Type-3 composite cylinders for CNG and hydrogen storage depends on proper control of operating conditions, installation, inspection, maintenance, and handling procedures. Particular attention should be given to pressure and temperature limits, secure mounting, protection against mechanical and environmental damage, and correct installation of pressure-relief devices.

Regular visual and certification inspections are essential for the early detection of damage and for maintaining cylinder integrity throughout its service life. Safe filling and defueling procedures, together with appropriate grounding, ventilation, purging, and control of ignition sources, are critical for reducing fire, explosion, and asphyxiation risks.

Overall, the implementation of appropriate technical and safety procedures, in accordance with applicable standards, regulations, and manufacturer requirements, provides the basis for extending operational reliability, minimizing risks, and ensuring the safe long-term use of composite CNG and hydrogen storage systems in vehicles.

ACKNOWLEDGMENTS

This research was performed by the APVV project SK–SRB–25–0028 Implementation of the process of measuring diesel particulate matter during emission inspection in the Slovak Republic and Serbia; number 001147721/007, Republic of Serbia, Ministry of Science, Technological Development and Innovation. This work has been also performed and funded as a part of activities within the projects 451–03–33/2026–03/200107 and 451–03–34/2026–03/200107, supported by the Republic of Serbia, Ministry of Science, Technological Development and Innovation.

REFERENCES

- Aldhafeeri, T., Tran, M.-K., Vrolyk, R., Pope, M., & Fowler, M. (2020). A Review of Methane Gas Detection Sensors: Recent Developments and Future Perspectives. *Inventions*, 5(3), 28. <https://doi.org/10.3390/inventions5030028>
- European Parliament & Council of the European Union. (2019). *Regulation (EU) 2019/2144 of the European Parliament and of the Council of 27 November 2019 on type-approval requirements for motor vehicles and their trailers, and systems, components and separate technical units intended for such vehicles. Official Journal of the European Union*, L 325, 1–40.
- International Organization for Standardization. (2013). *Gas cylinders-High pressure cylinders for the on-board storage of natural gas as a fuel for automotive vehicles* (ISO Standard No. 11439:2013). <https://www.iso.org/obp/ui/en/#iso:std:iso:11439:ed-2:v1:en>
- International Organization for Standardization. (2013). *Gas cylinders-Inspection of the cylinder installation, and requalification of high pressure cylinders for the on-board storage of natural gas as a fuel for automotive vehicles* (ISO Standard No. 19078:2013).
- International Organization for Standardization. (2025). *Hydrogen fuel quality-Product specification* (ISO Standard No. 14687:2025).
- Loman, M., Harantová, V., & Milojević, S. (2026). Air Quality in Urban Mobility Hubs: An Analysis of Particulate Matter in Underground Transport Spaces. *Urban Science*, 10(7), 412. <https://doi.org/10.3390/urbansci10070412>
- Luxfer Gas Cylinders. (2018). *Carbon Composite Cylinder User Manual: Alternative Fuel Cylinders*.
- Milojević, S. (2017). Sustainable application of natural gas as engine fuel in city buses: Benefit and restrictions. *Journal of Applied Engineering Science*, 15(1), 81-88. <https://doi.org/10.5937/jaes15-12268>
- Milojević, S., Stopka, O., Orynycz, O., Tucki, K., Šarkan, B., & Savić, S. (2025). Exploitation and Maintenance of Biomethane-Powered Truck and Bus Fleets to Assure Safety and Mitigation of Greenhouse Gas Emissions. *Energies*, 18(9), 2218. <https://doi.org/10.3390/en18092218>
- Turek, M., Kalupová, B., Cempírek, V., Tůmová, K. & Abramović, B. (2024). Electromobility and the Environment in the Czech Republic. *LOGI – Scientific Journal on Transport and Logistics*, 15(1), <https://doi.org/10.2478/logi-2024-0018>
- UN ECE Regulation No. 110 Rev.3-CNG and LNG Vehicles. <http://www.unece.org/trans/main/wp29/wp29regs101-120.html>
- United Nations Economic Commission for Europe. (2019). *UN Regulation No. 134: Uniform provisions concerning the approval of motor vehicles and their components with regard to the safety-related performance of hydrogen-fuelled vehicles (HFCV)*.

